

# SCM Creator (+Github) - Feature #1875

## Bazaar support

20 Oct 2011 17:50 - Andriy Lesyuk

<b>Status:</b>	Closed	<b>Start date:</b>	20 Oct 2011
<b>Priority:</b>	Normal	<b>Due date:</b>	05 Nov 2011
<b>Assignee:</b>	Andriy Lesyuk	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.3.0		
<b>External issue:</b>			
<b>Description</b>			
The command for creating repo should be (thanks Mario Rui Luzeiro!):			
<pre>bzr new --feature-branches --create-prefix --format 2a LOCATION</pre>			

## History

### #1 - 03 Nov 2011 19:57 - Andriy Lesyuk

```
$ bzr new --help
bzr: ERROR: unknown command "new"
```

:S I guess I cannot use new...

What then? bzr init or bzr init-repository?..

### #2 - 03 Nov 2011 20:10 - Andriy Lesyuk

What protocols are supported? sftp://, bzr+ssh://? Else? What about http://? Using %r{(?:sftp|bzr(?:\+[a-z]+)?):/}...

### #3 - 03 Nov 2011 20:13 - Andriy Lesyuk

- Status changed from Open to In Progress

- % Done changed from 0 to 20

Using bzr init-repository <custom options> <path>...

### #4 - 04 Nov 2011 10:17 - Andriy Lesyuk

- % Done changed from 20 to 70

### #5 - 05 Nov 2011 12:48 - Andriy Lesyuk

- Due date set to 05 Nov 2011

- Status changed from In Progress to Closed

- % Done changed from 70 to 100

I believe support for Bazaar has been implemented!

**#6 - 05 Nov 2011 16:09 - Mario Luzeiro**

Andriy Lesyuk wrote:

:S I guess I cannot use new...  
What then? bzd init or bzd init-repository?..

I get the new from the command line of bazaar explorer. I don't understand it at all, probably it inits at local machine some information about the repository it creates remotely.

```
bzd --help new  
bzd init-workspace [LOCATION]
```

we should understand this options better.. or ask some one that know it better.  
Also.. there is any way you can setup in redmine your own init command line? in configuration of plugin. that would be nice.

**#7 - 05 Nov 2011 16:10 - Mario Luzeiro**

Andriy Lesyuk wrote:

What protocols are supported? sftp://, bzd+ssh://? Else? What about http://? Using `%r{^(?:sftp|bzd(?:\:[a-z]+)?):/}`...

I'm not sre what you mean. Probably bazaar supports all of this protocols. I'm using redmine from turnkeylinux and it works with bzd://

**#8 - 08 Nov 2011 13:06 - Mario Luzeiro**

- *File Redmine\_bug\_CreateRepository01.png added*

Nothing happen after press repository.  
There is the log in attached image

**#9 - 08 Nov 2011 14:00 - Andriy Lesyuk**

Can you show me your Bazaar scm.yml configuration?.. I guess it's missing either path or (most likely) bzd...

**#10 - 09 Nov 2011 12:02 - Mario Luzeiro**

Andriy Lesyuk wrote:

Can you show me your Bazaar scm.yml configuration?.. I guess it's missing either path or (most likely) bzd...

I didn't touch this file.

```
bazaar:  
path: /var/lib/bazaar  
bzc: /usr/bin/bzc
```

This path should be the same as the others: /srv/repos/bzc  
Also I notice that I don't have any files in pre or post create/delete in /usr/local/bin/..

**#11 - 09 Nov 2011 12:14 - Mario Luzeiro**

- File *Redmine\_bug\_CreateRepository02.png* added

Now in bazaar the creation button does not appear.  
See attach image.

**#12 - 09 Nov 2011 12:50 - Mario Luzeiro**

- File *Redmine\_bug\_CreateRepository03.png* added

Ok I setup it and press create new repository.  
The path field appears gray, the button is still visible  
but it didn't create the repository.

**Files**

---

Redmine_bug_CreateRepository01.png	16.3 KB	08 Nov 2011	Mario Luzeiro
Redmine_bug_CreateRepository02.png	19.1 KB	09 Nov 2011	Mario Luzeiro
Redmine_bug_CreateRepository03.png	17.1 KB	09 Nov 2011	Mario Luzeiro