

## WikiNG - Feature #2251

### Configurable macros

09 Oct 2013 09:34 - Andriy Lesyuk

<b>Status:</b>	Closed	<b>Start date:</b>	09 Oct 2013
<b>Priority:</b>	Normal	<b>Due date:</b>	12 Oct 2013
<b>Assignee:</b>	Andriy Lesyuk	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	1.0.0b		
<b>External issue:</b>	#2854, #5171		

#### Description

The syntax of a macro is:

```
{{name(argument1,option1=value1,argument2)
Some text
}}
```

A macro gets implemented using API in a plugin. But unless the macro requires some server-side calculations it should be possible to build it runtime though...

For example, a user can define the code:

```
<blockquote class="twitter-tweet"><p><...></p>&mdash; <{full_name}> (@<{username}>) <a href="https://twitter.com/twitterapi/status/<{status}>"><{date}></a></blockquote>
<script src="//platform.twitter.com/widgets.js" charset="utf-8"></script>
```

Where:

- <{option}> – option by name
- <[1]> – argument by number (starting from 1)
- <...> – text

And then use:

```
{{tweet(full_name=Twitter API,username=twitterapi,status=133640144317198338,date=November 7 2011)
Search API will now always return "real" Twitter user IDs. The with_twitter_user_id parameter is no longer necessary. An era has ended.
}}
```

*Disclaimer: This is just an example.*

#### Associated revisions

**Revision 56 - 12 Oct 2013 23:22 - Andriy Lesyuk**

Custom Wiki macros (#2251)

#### History

**#1 - 09 Oct 2013 17:14 - Andriy Lesyuk**

Thinking about [this icon](#).

**#2 - 11 Oct 2013 10:40 - Andriy Lesyuk**

- Assignee set to *Andriy Lesyuk*
- Target version set to *1.0.0b*
- % Done changed from *0* to *70*
- External issue set to *#2854, #5171*

**#3 - 12 Oct 2013 23:23 - Andriy Lesyuk**

- Due date set to *12 Oct 2013*
- Status changed from *Open* to *Closed*
- % Done changed from *70* to *100*