WikiNG - Feature #2251

Configurable macros

09 Oct 2013 09:34 - Andriy Lesyuk

Status:	Closed	**Start date:**	09 Oct 2013
Priority:	Normal	**Due date:**	12 Oct 2013
Assignee:	Andriy Lesyuk	**% Done:**	100%
Category:		**Estimated time:**	0.00 hour
Target version:	1.0.0b		
External issue:	#2854, #5171		

Description

The syntax of a macro is:

```
{{name(argument1,option1=value1,argument2)
Some text
}}
```

A macro gets implemented using API in a plugin. But unless the macro requires some server-side calculations it should be possible to build it runtime though...

For example, a user can define the code:

```
<blockquote class="twitter-tweet"><p><...></p>&mdash; <{full_name}> (@<{username}>) <a href="https
://twitter.com/twitterapi/status/<{status}>"><{date}></a></blockquote>
<script src="//platform.twitter.com/widgets.js" charset="utf-8"></script>
```

Where:

- <{option}> – option by name
- <[1]> – argument by number (starting from 1)
- <...> – text

And then use:

```
{{tweet(full_name=Twitter API,username=twitterapi,status=133640144317198338,date=November 7 2011)
Search API will now always return "real" Twitter user IDs. The with_twitter_user_id parameter is n
o longer necessary. An era has ended.
}}
```

Disclaimer: This is just an example.

Associated revisions

Revision 56 - 12 Oct 2013 23:22 - Andriy Lesyuk

Custom Wiki macros (#2251)

History

#1 - 09 Oct 2013 17:14 - Andriy Lesyuk

Thinking about this icon.

#2 - 11 Oct 2013 10:40 - Andriy Lesyuk

- Assignee set to Andriy Lesyuk

- Target version set to 1.0.0b

- % Done changed from 0 to 70

- External issue set to #2854, #5171

#3 - 12 Oct 2013 23:23 - Andriy Lesyuk

- Due date set to 12 Oct 2013

- Status changed from Open to Closed

- % Done changed from 70 to 100